



Sample image

KG127

Type Size: S2

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Bolt terminal/Screw terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage Ui

Voltage (V)	AC / DC
1000	AC

Rated impulse withstand voltage Uimp

Voltage (kV)	Overtoltage category	Pollution degree	Supply system	Function
8	III	3	Valid for lines with grounded common neutral termination	Switch / Switch disconnecter

Rated uninterrupted current Iu/Ith

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
125	50	55	Ambient temperature +50°C during 24 hours with peaks up to +55°C

Conventional enclosed thermal current Ithe

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
125	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--

Rated operational current Ie

Utilization category	Voltage (V)	Current (A)
AC-32A	20 - 400	125
AC-20A	1000	125
AC-21A	20 - 690	125
AC-22A	220 - 500	125
AC-22A	660 - 690	100

Rated operational power

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-3	220 - 240	3	3	22
AC-3	380 - 440	3	3	37
AC-3	500 - 500	3	3	45
AC-3	660 - 690	3	3	30
AC-23A	220 - 240	3	3	30
AC-23A	380 - 440	3	3	45
AC-23A	500 - 500	3	3	55
AC-23A	660 - 690	3	3	37

Max. Fuse rating IEC

Fuse characteristic	No. of Fuses	Current (A)
gG	1	125

UL60947-4-1, UL508

Rated insulation voltage Ui

Voltage (V)	AC / DC
600	AC

Rated thermal current

Current (A)	Ambient temperature (°C)	Additional Text
150	0 - 40	--

General Information
Text

- The operating handle and position indicating means to be used with these manual motor controllers should be provided from the manufacturer, or the operating handle and position indicating means to be used should have been previously evaluated in combination with the manual motor controllers.

CSA

Rated insulation voltage Ui

Voltage (V)	AC / DC
600	AC

Rated thermal current			
Current (A)	Ambient temperature (°C)	Additional Text	
150	0 - 40	-	

GENERAL TECHNICAL INFORMATION

Tightening torque of screws	
tightening torque (Nm)	tightening torque (lb-in)
14	125

Rated short-time withstand current Icw	
Time (s)	Current (A)
1	2500


Size of conductor				
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm ²) or (AWG/kcmil)	Material of the wire
Flexible wire	Max.	1	70mm ²	Copper
Flexible wire	Max.	1	AWG 2/0	Copper
Single-core or stranded wire	Max.	1	95mm ²	Copper
Single-core or stranded wire	Max.	1	AWG 3/0	Copper
Flexible wire with sleeve	Max.	1	70mm ²	Copper

Approbations	
Specification	Marking

EAC	
CE marking	

UK Directives	
IEC 60947-3; EN 60947-3; VDE 0660 Teil107	IEC 60947-3 EN 60947-3

IEC 60947-6-1	IEC 60947-6-1 EN 60947-6-1
---------------	---------------------------------------

UL 60947-4-1; CSA C22.2 No. 60947-4-1	
---------------------------------------	---

CSA C.22.2 No.14	
------------------	---

GB/T14048.3	
-------------	---

Power loss per pole	
Power (W)	
3,10	

Conditions during transport and storing		
Minimum temperature (°C)	Maximum temperature (°C)	additional requirements
-40	85	In case of temperatures below -5°C no shock load permissible

General Information

- Text**
- The wiring aid has to be removed before voltage is applied!
 - EMC Note: This device is suitable for use in environment A and B.
 - Terminals with factory fitted jumper links are tightened during production for loss prevention. When opening the terminal clamps, make sure that no factory fitted links get lost and that all wire connections are properly seated.
 - After wiring, ALL terminal screws must be tightened to the specified torque values.
 - The protection class of the selected mounting type may vary if optional extras are used.
 - Do not lubricate or treat contacts.
 - Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.

Operating temperature	
Min. Temperature [°C]	Max. Temperature [°C]
-5	55

Dimensions ring cable lug

A(mm)	20,00 mm
A(mm)	25,00 mm